



MIL-PRF-680C TYPE II
«DEGREASING SOLVENT»
LOW ODOR SOLVENT – HIGH FLASH POINT
QPL PRODUCT

Description – Intended Use

All the products under specification MIL-PRF-680C are hydrocarbon-based solvents used as degreasers and cleaners for painted and unpainted metal surface and degreasing of machine parts in equipment maintenance.

TYPE II (low odor with high flash point solvent) is intended for use where a solvent with a higher flash point is desired. It is recommended over Type I for safety and regulatory reasons.

Advantages: MIL-PRF-680C Type II has replaced PD-680 Type II and has the following advantages:

- ◆ Safe to personnel contains less than 0,01% aromatics in comparison to PD-680 Type II that contains approximately 20%.
- ◆ Almost odorless.
- ◆ Much safer to metals in comparison to PD-680 Type II.
- ◆ More efficient.
- ◆ Since it does not contain aromatics, it is much safer to the environment.
- ◆ **Is enlisted on the Qualified Product List (QPL) in accordance with specification MIL-PRF-680C TYPE II.**
- ◆ **Also, meets the specification A-A-59601 TYPE II.**

Product properties:

Flash point °C, min	61
Distillation range °C	185-211
Kauri-butanol value	30
Copper Corrosion, max	1b
Sandwich Corrosion, max	1
Acidity	Neutral
Doctor Test	Negative
Aromatic content, by volume %, max	0,01
Specific Gravity	0,79 ± 0,01
Color	30
Odor	Low and non-residual
Soil Cleaning efficiency, min	85%

Usage: Used neat by brush, spray or dipping. Do not rinse off allow to dry.

Safety: Avoid contact with skin and eyes. For further instructions refer to MSDS.

Packaging: MIL-PRF-680C TYPE II is offered in 20 or 25 liter pails and 210 liter drums.

Note: Our company manufactures all 5 types of MIL-PRF-680C, Type I, Type II, Type III, Type IV and Type V in conformance with the specification MIL-PRF-680C.